

Directional Coupler

ZDC-2375

75Ω

50 to 100 MHz



CASE STYLE: M22
Connectors Model
BNC ZDC-2375
BRACKET (OPTION "B")
BRACKET (OPTION "BR")

Maximum Ratings

Operating Temperature -55°C to 100°C

Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

INPUT	3
OUTPUT	2
COUPLED	1


Features

- excellent directivity, 35 dB typ.
- rugged shielded case

Applications

- VHF
- instrumentation
- amateur radio

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
2.25	1.38	1.24	.50	.150	3.100	.138	1.238
57.15	35.05	31.50	12.70	3.81	78.74	3.51	31.45
J	K	L	M	N	P	S	wt
3.25	.10	.40	1.15	1.86	.64	.150	grams
82.55	2.54	10.16	29.21	47.24	16.26	3.81	74.0




Directional Coupler Electrical Specifications

FREQ. RANGE (MHz)	COUPLING (dB)		MAINLINE LOSS ¹ (dB)		DIRECTIVITY (dB)		VSWR (:1)	POWER INPUT (W)
	Nom.	Flatness	Typ.	Max.	Typ.	Min.		
f _L -f _U								
50-100	10.5±0.3	±0.2	1.1	1.3	35	30	1.3	4.0


1. Mainline loss includes theoretical power loss at coupled port.

Typical Performance Data

Frequency (MHz)	Mainline Loss (dB) In-Out	Coupling (dB) In-Cpl	Directivity (dB)	Return Loss (dB)		Cpl
				In	Out	
50.00	0.99	10.57	52.45	26.22	18.63	17.21
54.00	1.00	10.58	54.23	25.62	18.48	16.93
58.00	1.00	10.58	52.93	25.06	18.35	16.67
62.00	1.01	10.59	53.45	24.52	18.21	16.40
66.00	1.01	10.60	54.40	24.05	18.07	16.14
71.00	1.01	10.61	55.26	23.47	17.89	15.82
76.00	1.01	10.62	53.83	22.93	17.72	15.51
81.00	1.02	10.63	53.81	22.42	17.53	15.19
86.00	1.02	10.64	55.09	21.94	17.36	14.89
100.00	1.04	10.68	53.96	20.73	16.84	14.08



Electrical Schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

