

# Coaxial High Power Amplifier

## HPA-25W-272+

50Ω    25W    20 to 2700 MHz

### The Big Deal

- High output power at saturation, 25W typ.
- High gain, 50 dB typ.
- Excellent directivity, 40 dB typ.
- Rugged 2U rack mount case style with internal fans
- Operates from AC line power: 85-264V
- Built-in over-temperature protection



CASE STYLE: NG1942-1

### Product Overview

The HPA-25W-272+ is a high power, rack mount amplifier with a built-in AC power supply which can be used for a wide variety of laboratory testing applications. This rugged amplifier is capable of amplifying signals up to 25W output power over its entire operating bandwidth of 20 – 2700 MHz. Built-in safety features include fans alarms and automatic shut down mechanism to prevent damage in the event of excessive internal temperatures. The amplifier's output stage is further protected in the event of a fault condition, allowing high power operation for up to 5 minutes into an OPEN or SHORT load (refer to the maximum input power specifications).

### Key Features

Feature	Advantages
Wideband frequency range	20 – 2700 MHz bandwidth covers popular wireless communications, SATCOM and radar bands in a single instrument, useful for many test applications.
25W output power at saturation	Supports high power test applications such as EMI, max power handling, and reliability testing
High Gain	50 dB typical gain allows the HPA-25W-272+ to be driven to full output power with nearly all commercially available signal generators
A/C Power	Operating from standard AC line power supply - the HPA-25W-272+ can be powered from 85-264V at 47~63 Hz making this HPA versatile in supporting global markets
Cooling system	Front to back forced air cooling fans makes this ideal for usage in test equipment racks.
Built-in protection	The unit shuts OFF when the internal amplifier reaches a preset temperature of 85±5°C, preventing damage to the amplifier and providing added reliability.
CE marked	Meets conformity standards for sale within the European Economic Area (EEA).



# Coaxial High Power Amplifier

## HPA-25W-272+

50Ω 25W 20 to 2700 MHz

### Features

- High output power at saturation, 25W typ.
- High gain, 50 dB typ.
- Excellent directivity, 40 dB typ.
- Rugged 2U rack mount case style with internal fans
- Operates from AC line power: 85-264V
- Built-in over-temperature protection
- CE marked

### Applications

- Laboratory test instrument
- RF Power stress test
- EMI and antenna testing
- Reliability testing



CASE STYLE: NG1942-1

Model No.	Description
HPA-25W-272+	High Power Amplifier w/ N-Type Connectors

#### Included Accessories

CBL-3W-XX	AC Power Cord
-----------	---------------

**+RoHS Compliant**  
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Electrical Specifications at 25°C

Parameter	Condition	Min.	Typ.	Max.	Units
Frequency Range		20	—	2700	MHz
Gain	20 - 2700 MHz	44	50	56	dB
Gain Flatness	20 - 2700 MHz	—	±1.5	±2.1	dB
Output Power at 1dB compression <sup>1</sup>	20 - 2700 MHz	—	+38	—	dBm
Saturated Output Power <sup>1</sup>	20 - 2700 MHz	—	+44	—	dBm
Noise Figure	20 - 2700 MHz	—	10	—	dB
Output third order intercept point	20 - 2700 MHz	—	+50	—	dBm
Input VSWR	20 - 2700 MHz	—	1.3	—	:1
Output VSWR	20 - 2700 MHz	—	2.5	—	:1
Directivity	20 - 2700 MHz	—	40	—	dB
Line Supply	47-63 Hz		85/264		V
Power Consumption	110/220V	—	200	300	W

1. Power measured of fundamental tone only. Does not include power contribution of harmonics signals.

### Maximum Ratings<sup>2</sup>

Parameter	Ratings
Operating Temperature	0°C to 50°C
Storage Temperature	-20°C to 70°C (non condensing)
Input RF Power (no damage)	+5 dBm <sup>3</sup> -10 dBm <sup>4</sup>

2. Specifications apply to CW signals only permanent damage may occur if any of these limits are exceeded.

3. Into 50 ohm load

4. Into open or short load, for up to 5 minutes.


### D-Sub Male Connector Pin Functions (Front Panel)

Pin #	Function	TTL Logic Level	
		Low	High
1	Temperature Alarm	Normal	Alarm Shutdown
2	Fan Alarm	Normal	Fault
3	Ground	—	—
4-9	No connection	—	—

### LED Indicators (Front Panel)

Name	Color	LED State	
		Off	On
Power	Green	Power off	Power on
Temp	Red	Normal	Alarm Shutdown
Fan	Red	Normal	Fault

## Outline Drawing



## Outline Dimensions (inch)

	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	wt
	3.46	18.91	20.2	.12	.89	17.13	2.25	18.31	2.58	3.36	2.48	6.90	5.12	1.73	1.30	3.31	2.06	grams
	88.0	480.4	513.0	3.0	22.7	435.0	57.2	465.0	65.5	85.4	62.9	175.2	130.0	44.0	33.0	84.1	52.4	13910

## Ordering, Pricing & Availability Information see our web site

Model	Description
HPA-25W-272+	Rack Mount High Power Amplifier







Included Accessories	Description
CBL-3W-XX	AC Power Cord (Select one power cord from below with each Rack Mount HPA)

AC Power Cords	Description
CBL-3W-US	US Power Cord
CBL-3W-EU	EU Power Cord
CBL-3W-UK	UK Power Cord



## Typical Performance Data

FREQUENCY (MHz)	GAIN (dB)	DIRECTIVITY (dB)	VSWR (:1)		POUT at 1 dB COMPR. (dBm)	POUT at Saturation (dBm)	NOISE FIGURE (dB)	OIP3 (dBm)
			IN	OUT				
20	51.7	26.0	1.17	3.54	40.5	43.2	12.7	50.1
100	50.3	46.0	1.19	3.54	39.3	43.5	11.4	49.3
500	50.2	38.0	1.10	4.40	37.6	44.9	10.4	48.7
1000	51.1	36.0	1.05	1.64	40.4	47.1	10.2	50.7
1500	51.0	27.0	1.13	1.27	40.7	46.8	10.2	51.0
2000	49.9	29.0	1.06	2.54	39.4	46.7	10.4	49.3
2500	50.1	39.0	1.27	1.54	41.3	47.4	10.7	49.2
2700	49.4	50.0	1.26	1.36	40.0	45.4	10.8	48.4









### Additional Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

## Typical Performance Data


Frequency (MHz)	Gain (dB)	Directivity (dB)	VSWR In (:1)	VSWR Out (:1)	Noise Figure (dB)	Pout at 1dB Compression (dBm)	Pout at Saturation (dBm)	Output IP3 (dBm)
20	51.72	25.78	1.17	3.71	12.74	40.48	43.20	50.06
30	51.04	21.61	1.22	4.34	12.40	39.35	43.50	49.89
40	50.76	18.31	1.18	3.38	12.15	39.47	43.65	50.10
50	50.60	19.89	1.19	3.39	11.94	39.37	43.43	49.72
60	50.69	22.89	1.21	3.55	11.86	39.87	43.25	49.48
70	50.49	21.40	1.20	3.58	11.63	39.33	43.51	49.68
80	50.34	15.33	1.18	3.49	11.59	39.64	43.61	49.86
90	50.23	21.15	1.19	3.52	11.49	39.77	43.47	49.56
100	50.31	45.64	1.19	3.70	11.38	39.35	43.31	49.32
200	50.70	29.39	1.21	3.91	10.47	39.06	43.71	49.53
300	50.55	37.63	1.20	3.89	10.41	38.41	44.23	49.26
400	49.48	33.60	1.13	4.22	10.28	37.42	44.63	48.50
500	50.17	37.59	1.10	4.42	10.39	37.55	44.85	48.67
600	50.31	38.00	1.01	4.39	10.23	38.20	44.97	48.76
700	51.43	39.48	1.06	2.86	10.31	39.54	46.15	49.57
800	50.82	43.65	1.06	2.54	10.20	39.51	46.28	49.98
900	50.69	39.75	1.11	1.85	10.23	39.73	46.50	50.27
1000	51.07	36.28	1.05	1.63	10.23	40.40	47.08	50.69
1100	50.79	34.47	1.15	1.27	10.18	40.29	46.45	50.87
1200	49.90	37.51	1.04	1.18	10.16	40.43	46.28	50.86
1300	49.17	30.24	1.04	1.09	10.24	40.44	46.67	50.84
1400	49.68	24.55	1.12	1.08	10.18	40.81	46.97	51.19
1500	51.04	27.41	1.13	1.26	10.21	40.73	46.83	50.99
1600	51.97	29.53	1.24	1.34	10.24	41.10	47.82	50.97
1700	51.52	22.03	1.26	1.96	10.38	40.46	46.67	49.94
1800	51.04	32.95	1.26	2.09	10.24	40.42	47.02	49.81
1900	49.94	27.04	1.27	2.83	10.52	39.61	46.86	49.20
2000	49.94	29.12	1.06	2.65	10.37	39.43	46.71	49.28
2100	49.98	28.70	1.17	3.15	10.45	39.22	46.47	49.06
2200	50.30	37.82	1.20	2.85	10.45	40.07	46.55	48.84
2300	50.37	26.57	1.13	2.61	10.48	41.02	46.98	49.26
2400	50.40	28.81	1.29	2.24	10.54	41.64	47.55	49.43
2500	50.14	39.06	1.27	1.53	10.62	41.33	47.44	49.20
2600	49.30	45.33	1.09	1.40	10.59	40.59	46.62	49.03
2700	49.43	49.30	1.26	1.42	10.73	39.96	45.39	48.39

## Typical Performance Curves



## Outline Dimensions

NG1942-1



CASE #	A	B	C	D	E	F	G	H	J	K	L
NG1942-1	3.46 (88.0)	18.91 (480.4)	20.2 (513.0)	.12 (3.0)	.89 (22.7)	17.13 (435.0)	2.25 (57.2)	18.31 (465.0)	2.58 (65.5)	3.36 (85.4)	2.48 (62.9)

CASE #	M	N	P	Q	R	S	T	WT, GRAMS
NG1942-1	6.90 (175.2)	5.12 (130.0)	1.73 (44.0)	1.30 (33.0)	3.31 (84.1)	2.06 (52.4)	-- --	13910

Dimensions are in inches (mm). Tolerances: 2Pl.  $\pm .03$ ; 3Pl.  $\pm .015$

### Note:

- Case material: Aluminum alloy.
- Finish: Powder coating, Color: White.



INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-0° to 50° C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-20° to 70° C (non condensing)	Individual Model Data Sheet