


Ultra High Dynamic Range Monolithic Amplifier Die

PHA-13HLN-D+

50Ω 1MHz to 1 GHz

The Big Deal

- Ultra-High IP3, +43 dBm typ.
- Medium Power, +28.7dBm typ.
- Excellent Noise Figure, 1.1 dB typ.
- Operates over +3 to +8V DC



Product Overview

PHA-13HLN-D+ (RoHS compliant) is an advanced wideband amplifier Die fabricated using E-PHEMT technology and offers extremely high dynamic range over a broad frequency range and with low noise figure. In addition, the PHA-13HLN-D+ has good input and output return loss over a broad frequency range.

Key Features

Feature	Advantages
Broad Band: 1MHz to 1 GHz	Broadband covering primary wireless communications bands: Cellular, VHF, UHF
Extremely High IP3 38.4 dBm typical at 1MHz 43 dBm typical at 0.5GHz	The PHA-13HLN-D+ matches industry leading IP3 performance relative to device size and power consumption. The combination of the design and E-PHEMT Structure provides enhanced linearity over a broad frequency range as evidence in the IP3 being approximately 15 dB above the P1dB point. This feature makes this amplifier ideal for use in: <ul style="list-style-type: none">• Driver amplifiers for complex waveform up converter paths• Drivers in linearized transmit systems• Secondary amplifiers in ultra-High Dynamic range receivers
Low Noise Figure: 1.1dB at 0.5 GHz	Enables lower system noise figure performance
High P1dB 28.7 dBm at 0.5 GHz	High P1dB, High OIP3, Low NF results in a very dynamic range preventing amplifier saturation under strong interfering signals. It can also be used to drive mixers requiring high drive
Unpackaged Die	Enables the user to integrate the amplifier directly into hybrids

Ultra High Dynamic Range Monolithic Amplifier Die

PHA-13HLN-D+

50Ω 1MHz to 1 GHz

Product Features


- High IP3, 43 dBm typ. at 0.5GHz
- Gain, 22.7 dB typ. at 0.5GHz
- High Pout, P1dB 28.7 dBm typ. at 0.5GHz
- Low noise figure, 1.1 dB at 0.5GHz
- Operates over +3 to +8V DC

Typical Applications

- Base station infrastructure
- CATV
- Cellular

General Description

PHA-13HLN-D+ (RoHS compliant) is an advanced wideband amplifier Die fabricated using E-PHEMT technology and offers extremely high dynamic range over a broad frequency range and with low noise figure. In addition, the PHA-13HLN-D+ has good input and output return loss over a broad frequency range.




+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Ordering Information: Refer to Last Page

Simplified Schematic and Pad description



Pad#	Function	Description
2	RF-IN	RF input pad. This pad requires the use of an external DC blocking capacitor.
4	RF-OUT & DC-IN	RF output pad and bias pad. DC voltage is present on this pad, therefore, a DC blocking capacitor is necessary for proper operation. An RF choke is needed to feed DC bias without loss of RF signal due to the bias connection.
1,3 & Bottom of Die	Ground (GND)	Ground

Bonding Pad Position



Dimensions in μm, Typical

L1	L2	L3	L4	H1	H2	H3	H4	Thickness	Pad#1 Ground Size	Pad#3 Ground Size	RF In & RF Out + DC Pad
85.5	160.5	704.5	790	85.5	495.2	924.5	1010	100	240 X 90	230 x 90	90 x 290

Note: 1. Bond Pad material - Gold
2. Bottom of Die - Gold plated



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. OR
M166553
PHA-13HLN-D+
WP/RS/CP
180320
Page 2 of 6

Electrical Specifications^{1,2} at 25°C, unless noted

Parameter	Condition (GHz)	Vd=8V ¹			Vd=5V ¹			Vd=3V ¹	Units
		Min.	Typ.	Max.	Min.	Typ.	Max.		
Frequency Range		1		1000	1		1000	1-1000	MHz
Gain	1		25.0			24.6		23.7	dB
	20		24.3			24.0		23.3	
	250		23.0			22.8		22.1	
	500		22.7			22.4		21.5	
	1000		20.4			20.1		18.7	
Input Return Loss	1		10.8			10.3		9.4	dB
	20		15.8			15.4		14.6	
	250		16.7			17.5		17.9	
	500		17.5			17.4		14.7	
	1000		10.5			10.2		7.9	
Output Return Loss	1		11.2			11.3		11.0	dB
	20		18.8			19.1		21.5	
	250		17.7			17.7		20.2	
	500		29.4			23.9		20.0	
	1000		9.0			8.9		7.8	
Reverse isolation	500		26.3			26.1		25.7	dB
Output Power @ 1 dB compression	1		26.2			21.3		15.1	dBm
	20		27.3			23.0		16.9	
	250		28.4			24.4		19.5	
	500		28.7			24.5		19.5	
	1000		27.4			24.2		18.7	
Output IP3 ²	1		38.4			37.0		30.6	dBm
	20		41.7			40.2		33.3	
	250		43.5			40.2		33.4	
	500		43.0			39.0		32.3	
	1000		42.2			36.4		28.6	
Noise Figure	1		3.0			3.1		3.0	dB
	20		1.2			1.2		1.1	
	250		1.1			0.9		0.9	
	500		1.1			1.0		1.0	
	1000		1.4			1.2		1.3	
Device Operating Voltage			8.0			5.0		3.0	V
Device Operating Current		—	234.1	—		138.9		71.2	mA
Device Current Variation vs. Temperature ³			-100.6			21.7		30.3	µA/°C
Device Current Variation vs Voltage			0.0155			0.0338		0.0338	mA/mV
Thermal Resistance, junction-to-ground lead Junction-to-ground lead at 85°C stage temperature			23.3			23.3		23.3	°C/W


1. Measured on Mini-Circuits Characterization test board. Die packaged in industry standard SOT-89 package and soldered on TB-969-13HLN+. See Characterization Test Circuit (Fig. 1)
 2. Tested at Pout= 0 dBm / tone.
 3. (Current at 85°C — Current at -45°C)/130

Absolute Maximum Ratings⁴

Parameter	at 8V	at 3V&5V
Operating Temperature (ground lead)	-40°C to 95°C	-40°C to 105°C
Power Dissipation ⁵	3.3W	3.3W
Input Power (CW)	+21 dBm (5 minutes max) ⁶ +10 dBm (continuous) for 1-10 MHz +11 dBm (continuous) for 10-1000 MHz	+21 dBm (5 minutes max) ⁶ +6 dBm (continuous) for 1-10 MHz +8 dBm (continuous) for 10-1000 MHz
DC Voltage on Pad 4	10V	10V

4. Permanent damage may occur if any of these limits are exceeded.
 Electrical maximum ratings are not intended for continuous normal operation.
 5. Up to 85°C, derate linearly to 2.5W at 95°C.
 6. Up to 85°C, derate linearly to +18 dBm at 95°C.

Characterization Test / Recommended Application Circuit



Components	Size	Value	Manufacturer	P/N
C1	0402	1.5 pF	Murata	GRM1555C1H1R5CZ01
C2	0603	2.2 uF		GRM188R61C225KE15
C3	0402	0.1uF		GRM155R71C104KA88
C4	0603	2.2 uF		GRM188R61C225KE15
C5	0402	1000 pF		GRM1555C1H102JA01
C6	0805	10 uF		GRM21BR61C106KE15
L1	1210	15 uH	Coilcraft	LQH32DN150K53L
L2	0603	5.1 nH	Coilcraft	0603CS-5N1XJL
R1	0402	1500 Ω	Koa	RK73H1ET1501F


Fig 1. Block Diagram of Test Circuit used for characterization. (DUT, Die packaged in SOT-89 package, soldered on Mini-Circuits Characterization test board TB-969-13HLN+) Gain, Return loss, Output power at 1dB compression (P1 dB) , output IP3 (OIP3) and noise figure measured using Agilent’s N5242A PNA-X microwave network analyzer.

Conditions:

1. Gain and Return loss: Pin= -25dBm.

Output IP3 (OIP3): Two tones, spaced 0.5 MHz apart, 0 dBm/tone at output.

Assembly Diagram



Assembly and Handling Procedure

1. Storage
Dice should be stored in a dry nitrogen purged desiccators or equivalent.
2. ESD
MMIC E-PHEMT amplifier dice are susceptible to electrostatic and mechanical damage. Die are supplied in antistatic protected material, which should be opened in clean room conditions at an appropriately grounded anti-static workstation. Devices need careful handling using correctly designed collets, vacuum pickup tips or sharp antistatic tweezers to deter ESD damage to dice.
3. Die Attach
The die mounting surface must be clean and flat. Using conductive silver filled epoxy, recommended epoxies are DieMat DM6030HK-PT/H579 or Ablestik 84-1LMISR4. Apply sufficient epoxy to meet required epoxy bond line thickness, epoxy fillet height and epoxy coverage around total die periphery. Parts shall be cured in a nitrogen filled atmosphere per manufacturer's cure condition. It is recommended to use antistatic die pick up tools only.
4. Wire Bonding
Bond pad openings in the surface passivation above the bond pads are provided to allow wire bonding to the dice gold bond pads. Thermosonic bonding is used with minimized ultrasonic content. Bond force, time, ultrasonic power and temperature are all critical parameters. Suggested wire is pure gold, 1 mil diameter. Bonds must be made from the bond pads on the die to the package or substrate. All bond wires should be kept as short as low as reasonable to minimize performance degradation due to undesirable series inductance.

Additional Detailed Technical Information <i>additional information is available on our dash board.</i>									
Performance Data	Data Table								
	Swept Graphs								
	S-Parameter (S2P Files) Data Set with and without port extension(.zip file)								
Case Style	Die								
Die Ordering and packaging information	<table border="0"> <tr> <td>Quantity, Package</td> <td>Model No.</td> </tr> <tr> <td>Small, Gel - Pak: 5,10,50,100 KGD*</td> <td>PHA-13HLN-DG+</td> </tr> <tr> <td>Medium†, Partial wafer: KGD*<1670</td> <td>PHA-13HLN-DP+</td> </tr> <tr> <td>Large†, Full Wafer</td> <td>PHA-13HLN-DF+</td> </tr> </table> <p>†Available upon request contact sales representative</p> <p>Refer to AN-60-067</p>	Quantity, Package	Model No.	Small, Gel - Pak: 5,10,50,100 KGD*	PHA-13HLN-DG+	Medium†, Partial wafer: KGD*<1670	PHA-13HLN-DP+	Large†, Full Wafer	PHA-13HLN-DF+
Quantity, Package	Model No.								
Small, Gel - Pak: 5,10,50,100 KGD*	PHA-13HLN-DG+								
Medium†, Partial wafer: KGD*<1670	PHA-13HLN-DP+								
Large†, Full Wafer	PHA-13HLN-DF+								
Environmental Ratings	ENV80								

*Known Good Dice ("KGD") means that the dice in question have been subjected to Mini-Circuits DC test performance criteria and measurement instructions and that the parametric data of such dice fall within a predefined range. While DC testing is not definitive, it does help to provide a higher degree of confidence that dice are capable of meeting typical RF electrical parameters specified by Mini-Circuits.

ESD Rating**

Human Body Model (HBM): Class 1B (pass 500V) in accordance with ANSI/ESD STM 5.1 - 2001

** Tested in industry standard SOT-89 package.

Additional Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp
- D. Mini-Circuits does not warrant the accuracy or completeness of the information, text, graphics and other items contained within this document and same are provided as an accommodation and on an "As is" basis, with all faults.
- E. Purchasers of this part are solely responsible for proper storing, handling, assembly and processing of Known Good Dice (including, without limitation, proper ESD preventative measures, die preparation, die attach, wire bonding and related assembly and test activities), and Mini-Circuits assumes no responsibility therefor or for environmental effects on Known Good Dice.
- F. Mini-Circuits and the Mini-Circuits logo are registered trademarks of Scientific Components Corporation d/b/a Mini-Circuits. All other third-party trademarks are the property of their respective owners. A reference to any third-party trademark does not constitute or imply any endorsement, affiliation, sponsorship, or recommendation by any such third-party of Mini-Circuits or its products.

*Typical Performance Data***NOTE: Use PDF Bookmarks to view DATA at required conditions****Definitions:**

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 8.00V, Id = 238.6mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
1	24.97	29.26	11.12	11.36	1.07	0.54	43.13	26.04	2.87
3	25.28	28.80	14.51	23.20	1.06	0.57	43.39	26.30	1.84
5	25.24	28.59	15.09	37.21	1.05	0.57	43.52	26.50	1.49
7	25.15	28.36	15.28	32.70	1.04	0.56	43.54	26.43	1.52
9	25.03	28.12	15.40	26.52	1.03	0.55	43.68	26.69	1.35
10	24.96	27.99	15.46	24.99	1.03	0.54	43.84	26.67	1.29
20	24.32	27.03	15.66	18.71	1.01	0.50	43.63	27.35	1.26
30	23.90	26.52	15.88	17.14	1.01	0.46	44.41	27.81	1.22
40	23.67	26.28	16.02	16.47	1.02	0.45	44.60	27.92	1.11
50	23.53	26.14	16.09	16.24	1.02	0.44	44.46	28.03	1.10
60	23.43	26.05	16.15	16.10	1.03	0.43	44.51	28.15	1.13
70	23.37	26.00	16.14	16.00	1.03	0.43	45.52	28.16	1.09
80	23.33	25.98	16.25	16.00	1.03	0.43	44.90	28.15	1.08
90	23.29	25.96	16.27	16.00	1.03	0.43	45.41	28.23	1.07
100	23.27	25.95	16.33	16.09	1.03	0.43	45.47	28.23	1.09
150	23.20	25.93	16.55	16.58	1.04	0.44	45.59	28.42	1.10
200	23.15	25.96	16.82	17.39	1.04	0.46	45.52	28.43	1.07
250	23.09	26.00	17.15	18.41	1.05	0.48	44.98	28.52	1.02
300	23.03	26.05	17.48	20.08	1.05	0.50	45.79	28.76	1.04
350	22.97	26.12	17.78	22.35	1.06	0.52	45.52	28.67	1.06
400	22.89	26.21	18.14	25.60	1.06	0.54	45.26	28.89	1.08
450	22.78	26.32	18.31	30.40	1.07	0.57	44.89	28.79	1.09
500	22.64	26.48	18.35	29.28	1.08	0.61	44.15	28.87	1.14
550	22.36	26.78	17.64	23.27	1.11	0.66	44.60	28.68	1.13
600	22.23	27.30	15.25	22.28	1.16	0.75	44.48	28.60	1.15
650	22.09	27.12	15.31	25.68	1.14	0.72	45.14	28.87	1.13
700	22.11	27.15	15.69	20.08	1.14	0.71	45.40	28.86	1.14
750	21.97	27.35	15.56	16.87	1.15	0.72	45.32	28.77	1.17
800	21.76	27.63	15.08	14.65	1.17	0.74	44.99	28.56	1.19
850	21.47	27.99	14.38	12.90	1.20	0.76	44.83	28.41	1.21
900	21.08	28.47	13.48	11.41	1.25	0.79	44.34	27.99	1.27
950	20.51	29.15	12.33	10.10	1.33	0.82	43.25	27.34	1.27
1000	19.64	30.16	10.86	9.00	1.48	0.87	41.51	26.46	1.30
1050	18.27	31.71	9.19	8.30	1.80	0.94	40.54	25.41	1.36
1100	16.71	33.41	7.59	8.58	2.36	1.03	40.36	25.66	1.47
1150	16.85	33.15	6.66	10.83	2.34	1.12	43.50	26.64	1.55
1200	18.23	31.71	6.46	16.08	1.88	1.16	45.12	27.62	1.64

Note: Test data of Die packaged in industry standard SOT-89 package

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 7.60V, Id = 226.05mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
1	24.96	29.26	11.07	11.38	1.07	0.55	43.10	25.53	--
3	25.26	28.80	14.41	23.26	1.06	0.57	43.46	25.78	--
5	25.22	28.59	14.97	37.86	1.05	0.57	43.53	25.85	--
7	25.13	28.36	15.16	32.77	1.04	0.56	43.64	26.06	--
9	25.01	28.12	15.31	26.50	1.03	0.55	43.77	26.05	--
10	24.94	27.99	15.41	24.97	1.03	0.54	43.90	26.02	1.25
20	24.31	27.02	15.65	18.68	1.01	0.49	44.32	26.89	1.22
30	23.88	26.51	15.89	17.12	1.01	0.46	45.14	27.37	1.18
40	23.65	26.27	16.07	16.43	1.02	0.45	45.96	27.49	1.07
50	23.52	26.12	16.19	16.22	1.02	0.44	45.11	27.60	1.07
60	23.42	26.05	16.24	16.08	1.03	0.43	44.75	27.73	1.09
70	23.36	26.00	16.21	15.96	1.03	0.43	45.60	27.72	1.05
80	23.31	25.97	16.27	15.96	1.03	0.43	45.45	27.80	1.06
90	23.28	25.94	16.33	15.97	1.03	0.43	45.41	27.80	1.05
100	23.26	25.93	16.40	16.05	1.03	0.43	45.66	27.78	1.07
150	23.19	25.92	16.65	16.54	1.04	0.44	45.38	27.98	1.07
200	23.14	25.94	16.92	17.33	1.04	0.46	45.30	28.08	1.05
250	23.08	25.98	17.24	18.34	1.05	0.47	44.94	28.07	0.99
300	23.02	26.03	17.53	19.96	1.05	0.50	45.92	28.32	1.02
350	22.96	26.10	17.87	22.18	1.05	0.52	45.19	28.23	1.03
400	22.87	26.19	18.25	25.24	1.06	0.54	45.13	28.46	1.04
450	22.77	26.30	18.37	29.27	1.07	0.57	45.06	28.44	1.05
500	22.62	26.46	18.40	28.25	1.08	0.61	44.24	28.42	1.06
550	22.34	26.76	17.67	22.86	1.11	0.66	44.88	28.32	1.07
600	22.21	27.28	15.28	21.80	1.16	0.75	45.02	28.19	1.09
650	22.08	27.10	15.35	25.29	1.14	0.72	45.58	28.44	1.11
700	22.10	27.12	15.73	20.06	1.13	0.71	46.05	28.44	1.10
750	21.96	27.32	15.60	16.89	1.15	0.72	45.93	28.46	1.15
800	21.75	27.59	15.12	14.67	1.17	0.74	45.83	28.26	1.17
850	21.46	27.95	14.42	12.93	1.20	0.76	45.64	28.03	1.19
900	21.07	28.43	13.53	11.43	1.25	0.79	45.32	27.63	1.24
950	20.51	29.09	12.38	10.12	1.32	0.82	43.99	27.13	1.23
1000	19.64	30.09	10.90	9.01	1.47	0.87	42.06	26.27	1.31
1050	18.29	31.63	9.22	8.29	1.78	0.94	41.29	25.21	1.34
1100	16.75	33.31	7.60	8.53	2.31	1.03	41.71	25.44	1.41
1150	16.88	33.05	6.68	10.72	2.30	1.12	44.01	26.37	1.49
1200	18.24	31.62	6.47	15.79	1.85	1.15	44.52	27.17	1.57

Note: Test data of Die packaged in industry standard SOT-89 package

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)








Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 8.40V, Id = 250.07mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
1	24.97	29.26	11.21	11.35	1.07	0.54	42.64	26.53	--
3	25.28	28.80	14.66	23.16	1.07	0.57	42.99	26.80	--
5	25.23	28.59	15.21	36.45	1.06	0.56	43.07	27.11	--
7	25.14	28.36	15.40	32.60	1.05	0.56	43.18	27.06	--
9	25.02	28.12	15.51	26.58	1.04	0.55	43.25	27.05	--
10	24.95	27.99	15.55	25.02	1.03	0.54	43.33	27.03	1.38
20	24.31	27.02	15.68	18.79	1.01	0.50	44.85	27.80	1.31
30	23.89	26.53	15.85	17.22	1.01	0.47	44.04	28.15	1.26
40	23.65	26.29	16.02	16.55	1.02	0.45	45.07	28.34	1.17
50	23.52	26.15	16.10	16.34	1.02	0.44	44.45	28.44	1.13
60	23.42	26.06	16.08	16.20	1.03	0.44	44.41	28.49	1.16
70	23.36	26.01	16.12	16.08	1.03	0.43	45.31	28.56	1.12
80	23.32	25.99	16.13	16.08	1.03	0.43	45.03	28.57	1.14
90	23.28	25.97	16.17	16.09	1.03	0.44	45.48	28.57	1.11
100	23.26	25.96	16.27	16.19	1.03	0.44	45.39	28.64	1.14
150	23.19	25.95	16.49	16.68	1.04	0.45	45.42	28.83	1.19
200	23.14	25.97	16.75	17.50	1.04	0.46	45.15	28.85	1.11
250	23.08	26.01	17.07	18.54	1.05	0.48	44.81	28.86	1.06
300	23.02	26.06	17.36	20.25	1.05	0.50	45.44	29.09	1.12
350	22.96	26.13	17.69	22.61	1.06	0.52	45.17	29.10	1.10
400	22.88	26.22	18.04	26.11	1.06	0.55	44.88	29.24	1.11
450	22.77	26.33	18.16	31.75	1.07	0.58	44.55	29.22	1.15
500	22.63	26.50	18.21	30.10	1.08	0.61	43.76	29.20	1.16
550	22.34	26.80	17.52	23.57	1.11	0.66	43.99	29.10	1.14
600	22.21	27.33	15.16	22.78	1.16	0.76	43.85	28.90	1.15
650	22.08	27.15	15.22	25.73	1.14	0.72	44.40	29.18	1.17
700	22.10	27.18	15.58	19.96	1.14	0.71	44.57	29.16	1.17
750	21.96	27.38	15.45	16.76	1.15	0.72	44.28	29.17	1.25
800	21.74	27.66	14.96	14.57	1.17	0.74	44.03	28.93	1.23
850	21.45	28.03	14.26	12.83	1.21	0.76	43.78	28.63	1.26
900	21.05	28.53	13.37	11.35	1.26	0.79	43.28	28.18	1.30
950	20.48	29.21	12.24	10.07	1.34	0.82	42.34	27.52	1.28
1000	19.60	30.23	10.77	9.00	1.49	0.87	40.80	26.64	1.36
1050	18.23	31.79	9.13	8.34	1.82	0.94	39.74	25.59	1.42
1100	16.68	33.49	7.56	8.67	2.39	1.04	39.34	25.82	1.52
1150	16.82	33.23	6.65	11.00	2.37	1.12	42.00	26.89	1.57
1200	18.19	31.80	6.44	16.45	1.90	1.16	43.95	27.88	1.62

Note: Test data of Die packaged in industry standard SOT-89 package

Typical Performance Curves



Note: Test data of Die packaged in industry standard SOT-89 package



All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85° C or -40° to 105° C or -55° to 105° C or -45° to 105° C Ambient Environment	Refer to Individual Model Data Sheet
Storage Environment (Die)	-65° to 150°C	Individual Model Data Sheet
Storage Environment(Packaging)	-40° to 70°C and 40 to 60% humidity (In Factory Shipped Package)	