



USB & ETHERNET

Mechanical Switch Assembly ZTM-6SP6T-12

50Ω DC to 12 GHz 6 x SP6T Rack-Mount SMA Female

THE BIG DEAL

- 6 x mechanical SP6T absorptive switches
- Convenient rack-mountable chassis
- SSH secure Ethernet communication
- Fail-safe / redundancy switching
- LED switch state indicators




Generic photo used for illustration purposes only

APPLICATIONS

- Benchtop and rack-mounted automated test systems
- 5G FR1, WiFi 6E MIMO, UWB, Bluetooth
- Military radio, radar & electronic warfare
- Microwave radio & cellular infrastructure
- Switch matrices

FUNCTIONAL BLOCK DIAGRAM



PRODUCT OVERVIEW

Mini-Circuits' ZTM-6SP6T-12 houses 6 independently controlled electro-mechanical SP6T switches. Each switch operates over a wide bandwidth, from DC to 12 GHz with high isolation and low insertion loss. The absorptive switches are failsafe, with a break-before-make configuration, and lifetime of 10 million switching cycles when used within the noted specifications.

The switches are housed in a compact 19-inch rack chassis, 3U height, with all SMA (female) RF connectors on the front. LED switch state indicators on the front panel enable visual display of all switch states. The switch assembly can be controlled via USB or Ethernet (supporting SSH, HTTP and Telnet network protocols). Full software support is provided, including our user-friendly GUI application for Windows and a full API with programming instructions for Windows and Linux environments.

The modular design of the ZTM series switch rack supports easy maintenance and re-configuration in the field, without the need to return the whole system to a Mini-Circuits facility. Custom switch configurations can be configured to fit any requirement, using Mini-Circuits' online configurator tool at www.minicircuits.com/WebStore/ztm.html.

KEY FEATURES

Feature	Advantages
Mechanical switches	Mechanical absorptive switches provide low loss, high isolation, high reliability, repeatable performance and internal termination of input signals on the disconnected paths
Flexible & modular design	Configure just the switch combination needed for your test application, with the flexibility to add or change switch modules in future as test requirements evolve.
Secure Ethernet communication	Support for SSH (secure shell protocol) provides a means for secure communication over Ethernet networks with strict security policies. HTTP & Telnet communication via Ethernet are also supported.
Fail-safe design	The switches revert to a known default state when the DC supply is removed, allowing their use in systems that must continue to operate safely in the event of power failure
Rack-mount chassis	Compact 3U height, 19" rack-mountable chassis suits integration in automated production test environments.

**ELECTRICAL SPECIFICATIONS AT +25°C (EACH SWITCH)**

Parameter	Conditions	Min.	Typ.	Max.	Units
Frequency Range	-	DC		12	GHz
Insertion Loss	DC - 6 GHz		0.15	0.25	dB
	6 - 8 GHz		0.20	0.30	
	8 - 12 GHz		0.25	0.45	
Isolation (Inactive Paths) ¹	DC - 6 GHz	80	95		dB
	6 - 8 GHz	80	90		
	8 - 12 GHz	80	90		
Return Loss ²	DC - 6 GHz		20		dB
	6 - 8 GHz		20		
	8 - 12 GHz		20		
Switching Time			25		ms
RF Input Power (Cold Switching)	Through path			20	W
	Into internal termination			1	
Switch Lifetime	100 mW hot switching ³	10			dBm
	1W hot switching		1		





1. Isolation measured between Com and any disconnected port. Example: Isolation for Com to 1 is the leakage measured at port 1 from a signal input at Com when the active switch path is set to Com to 2

2. Return loss into Com when active or ports 1-6 in any state; Com is reflective when disconnected

3. Hot switching power above this level will degrade the switch lifetime



TYPICAL PERFORMANCE GRAPHS





CONTROL INTERFACES

Ethernet Control	Supported Protocols	TCP / IP, SSH, HTTP, Telnet, DHCP, UDP (limited)
	Max Data Rate	100 Mbps (100 Base-T Full Duplex)
USB Control	Supported Protocols	HID – High Speed
	Min Communication Time	400 μs typ ¹

1. Based on the polling interval of the USB HID protocol (125 μs with 64 bytes per packet) and no other significant CPU or USB activity

SOFTWARE & DOCUMENTATION

Mini-Circuits' full software and support package including user guide, Windows GUI, API, programming manual and examples can be downloaded free of charge (refer to the last page for the download path).

A comprehensive set of software control options is provided:

- GUI for Windows – Simple software interface for control via Ethernet and USB
- Programming / automation via Ethernet
 - Complete set of control commands which can be sent via any supported protocol – simple to implement in the majority of modern programming environments
- Programming / automation via USB
 - DLL files provide a full API for Windows with a set of intuitive functions which can be implemented in any programming environment supporting .Net Framework or ActiveX
 - Direct USB programming is possible in any other environment (not supporting .Net or ActiveX)

Please contact testsolutions@minicircuits.com for support

MINIMUM SYSTEM REQUIREMENTS

Hardware	Intel i3 (or equivalent) or later
GUI (USB or Ethernet Control)	Windows 7 or later
USB API DLL	Windows 7 or later with support for Microsoft .Net Framework or ActiveX
USB Direct Programming	Windows 7 or later; Linux
Ethernet	Windows, Linux or macOS with Ethernet TCP / IP support

PROGRAMMING COMMANDS



The key ASCII / SCPI commands for control of the system for control via the Ethernet or USB API are summarized below (refer to the programming manual for full details):

Command / Query	Description
:MN?	Read model name
:SN?	Read serial number
:FIRMWARE?	Read firmware version
SP6T:[sw_label]:STATE:[port]	Set a switch state: <ul style="list-style-type: none"> • [sw_label] = Switch number (1 to 6) • [port] = The port to be connected to Com of the specified switch (1 to 6) • Example: SP6T:1:STATE:2
:SP6T:[sw_label]:STATE?	Get the state of all switches: <ul style="list-style-type: none"> • sw_label] = Switch number (1 to 6) • Example: SP6T:1:STATE?



GRAPHICAL USER INTERFACE (GUI) FOR WINDOWS - KEY FEATURES

- Connect via USB or Ethernet
- Run GUI in demo mode to evaluate the software without a hardware connection
- View and set all switch states at the click of a button
- Configure automated switching sequences
- Define custom switch and port labels
- Set switch power-up states
- Configure Ethernet settings





USB & ETHERNET

Mechanical Switch Assembly ZTM-6SP6T-12

50Ω DC to 12 GHz 6 x SP6T Rack-Mount SMA Female

ABSOLUTE MAXIMUM RATINGS

Parameter	Conditions	Limits	Units
Temperature	Operating	0 to +50	°C
	Storage	-20 to +60	
Input Power (No Damage)	Cold switching	20	W
	Hot switching	1	
	Into internal termination	1	

Permanent damage may occur if any of these limits are exceeded. Operating in the range between operating power limits and absolute maximum ratings for extended periods of time may result in reduced life and reliability.

POWER SUPPLY

Power Supply	AC mains input: 100-240 V, 50 / 60 Hz
Fuse	2A, 250V rating
Power Consumption	150W maximum

SWITCH STATE TABLE

Switch Command	Switch Path
:SP6T:x:STATE:0	All ports disconnected
:SP6T:x:STATE:1	COM to 1
:SP6T:x:STATE:2	COM to 2
:SP6T:x:STATE:3	COM to 3
:SP6T:x:STATE:4	COM to 4
:SP6T:x:STATE:5	COM to 5
:SP6T:x:STATE:6	COM to 6


x = switch number (1 to 6)

CONNECTIONS

Port	Connector
COM & 1-6 (each SP6T)	SMA female
USB	USB type B
Ethernet / LAN	RJ45
AC Input	IEC C14 inlet


COM = Common port
1-6 = input / output ports

FUNCTIONAL BLOCK DIAGRAM





CASE STYLE DRAWING



1. Case material: Aluminum (with protective coating to prevent corrosion).
2. Dimensions are in inches (mm). Tolerances: 2 Pl. ± .03 inch; 3 Pl. ± .015 inch.
3. Weight: 4535 grams.
4. Marking may contain features or characters for internal lot control.

PRODUCT MARKING*

Product Marking: ZTM-6SP6T-12

Unit ID Label: Serial number and other identification marks

*Marking may contain other features or characters for internal lot control



USB & ETHERNET

Mechanical Switch Assembly **ZTM-6SP6T-12**




Mini-Circuits






50Ω DC to 12 GHz 6 x SP6T Rack-Mount SMA Female

DETAILED MODEL INFORMATION IS AVAILABLE ON OUR WEBSITE [CLICK HERE](#)

Case Style	YD2861
Software, User Guide & Programming Manual	www.minicircuits.com/softwaredownload/ztm_ztm2.html
Environmental Rating	ENV55
Regulatory Compliance	<p>Refer to our website for compliance methodologies and qualifications</p>  <p>www.minicircuits.com/quality/environmental_introduction.html</p>

Contact Us: testsolutions@minicircuits.com

Included Accessories	Part Number	Description
	CBL-3W-xx	AC power cord (IEC C13 connector to local plug) Select one option from the list below. Please contact testsolutions@minicircuits.com if your region is not listed.
	USB-CBL-AB-7+	USB cable (6.8ft) type A to type B
	CBL-RJ45-MM-5+	Ethernet cable (5 ft)
	HT-4-SMA	SMA connector wrench (4" length)


AC Power Cord Options	Part Number	Description
	CBL-3W-US	USA NEMA 5-15 plug (type B) to IEC C13 connector
	CBL-3W-EU	Europe CEE 7/7 plug (type E/F) to IEC C13 connector
	CBL-3W-UK	UK BS-1363 plug (type G) to IEC C13 connector
	CBL-3W-AU	Australia & China AS/NZS 3112 plug (type I) to IEC C13 connector
	CBL-3W-IL	Israel SI-32 plug (type H) to IEC C13 connector

- NOTES**
- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 - Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 - The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the standard. Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Outline Dimensions

YD2861



CASE #	A	B	C	D	E	F	G	H	J	K	L	M	N
YD2861	5.22 (132.6)	19.00 (482.6)	13.00 (330.2)	.49 (12.4)	.13 (3.3)	1.00 (25.4)	1.00 (25.4)	17.00 (431.8)	5.02 (127.5)	2.250 (57.15)	18.280 (464.31)	.78 (19.8)	3.75 (95.3)

CASE #	P	Q	R	S	T	U	V	W	X	Y	Z	WT, GRAMS
YD2861	2.50 (63.5)	1.22 (31.0)	2.47 (62.7)	3.72 (94.5)	1.94 (49.3)	1.81 (46.0)	2.56 (65.0)	1.25 (31.8)	1.79 (45.5)	4.49 (114.0)	1.81 (46.0)	4535

Dimensions are in inches (mm) . Tolerances: 2 Pl. $\pm .03$; 3 Pl. $\pm .015$

Notes:

1. Case material: Aluminum alloy.
2. Finish: Clear chemical conversion coating



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com


RF/IF MICROWAVE COMPONENTS

SPDT Switch Options:


YD2861



SPDTA 18GHz



SPDTA 26GHz



SPDT 40GHz
SPDT 50GHz

Mini-Circuits®
ISO 9001 ISO 14001 CERTIFIED

ALL NEW
minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com


RF/IF MICROWAVE COMPONENTS

MTS (Transfer) Switch Options:


YD2861




MTS 18GHz



MTS 18GHz



MTS 26GHz
MTS 40GHz
MTS 50GHz



MTS 26GHz
MTS 40GHz
MTS 50GHz

Mini-Circuits®
ISO 9001 ISO 14001 CERTIFIED

ALL NEW
minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com


RF/IF MICROWAVE COMPONENTS

SP4T and SP6T Switch Options:

YD2861




SP4TA 18GHz




5x FEMALE CONNECTOR
26GHz SMA
40GHz 2.9mm
50GHz 2.4mm

SP4TA 26GHz
SP4TA 40GHz
SP4TA 50GHz



SP6TA 12GHz
SP6TA 18GHz



7x FEMALE CONNECTOR
26GHz SMA
40GHz 2.9mm
50GHz 2.4mm

SP6TA 26GHz
SP6TA 40GHz
SP6TA 50GHz



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site




The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com


RF/IF MICROWAVE COMPONENTS

SP8T Switch Options:

YD2861



SP8TA 12GHz



SP8TA 18GHz
SP8TA 26GHz

Mini-Circuits
ISO 9001 ISO 14001 CERTIFIED

ALL NEW
minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site



The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

RF/IF MICROWAVE COMPONENTS



Environmental Specifications **ENV55**

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-0° to 50° C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-20° to 60° C Ambient Environment	Individual Model Data Sheet
Operating and Storage Humidity	5% to 85% RH (non-condensing)	Ambient
Bench Handling Test	Bench Top Tip 45° & Drop	MIL-PRF-28800F
Transit Drop Test	Free Fall Drop, 20 cm (7.9 inches)	MIL-PRF-28800F Class 3