

Adapter 2.4mm-Male to 2.92mm-Male

24MR-KM+

Typical Performance Data

FREQ.	INSERTION LOSS	2.4mm-MALE VSWR	2.92mm-MALE VSWR
(GHz)	(dB)	(:1)	(:1)
0.01	0.01	1.01	1.01
0.05	0.01	1.01	1.01
0.10	0.01	1.01	1.01
1.00	0.03	1.03	1.03
2.00	0.04	1.04	1.04
3.00	0.04	1.04	1.05
4.00	0.05	1.04	1.05
5.00	0.05	1.02	1.03
6.00	0.05	1.02	1.02
7.00	0.06	1.05	1.05
8.00	0.07	1.09	1.08
9.00	0.09	1.12	1.09
10.00	0.10	1.14	1.08
11.00	0.10	1.13	1.06
12.00	0.10	1.11	1.07
13.00	0.09	1.08	1.10
14.00	0.09	1.06	1.10
15.00	0.10	1.06	1.08
16.00	0.12	1.09	1.03
17.00	0.11	1.13	1.04
18.00	0.11	1.16	1.09
19.00	0.11	1.16	1.10
20.00	0.15	1.13	1.08
21.00	0.16	1.10	1.01
22.00	0.16	1.07	1.07
23.00	0.14	1.08	1.17
24.00	0.14	1.09	1.22
25.00	0.20	1.06	1.21
26.00	0.20	1.02	1.16
27.00	0.17	1.06	1.07
28.00	0.15	1.13	1.02
29.00	0.16	1.17	1.06
30.00	0.15	1.16	1.09
31.00	0.15	1.11	1.09
32.00	0.14	1.06	1.10
33.00	0.16	1.04	1.08
34.00	0.20	1.07	1.08
35.00	0.22	1.14	1.14
36.00	0.21	1.22	1.21
37.00	0.22	1.26	1.25
38.00	0.30	1.24	1.22
39.00	0.28	1.18	1.19
40.00	0.27	1.13	1.14



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
 The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com



IF/RF MICROWAVE COMPONENTS

REV. OR
 24MR-KM+
 11/19/2025
 Page 1 of 1