

Typical Performance Data

FREQUENCY (GHz)	ATTENUATION (dB)	VSWR (:1)
0.01	5.98	1.08
0.02	5.98	1.08
0.04	5.98	1.08
0.06	5.98	1.08
0.08	5.98	1.08
0.10	5.98	1.08
0.20	5.98	1.08
0.40	5.98	1.08
0.60	5.98	1.08
0.80	5.98	1.08
1.00	5.98	1.08
1.20	5.98	1.08
1.40	5.98	1.08
1.60	5.98	1.08
1.80	5.98	1.08
2.00	5.99	1.08
3.00	5.98	1.08
4.00	5.98	1.08
5.00	5.98	1.08
6.00	5.98	1.07
7.00	5.97	1.07
8.00	5.97	1.07
9.00	5.97	1.07
10.0	5.97	1.07
11.0	5.97	1.06
12.0	5.99	1.05
13.0	6.02	1.05
14.0	6.02	1.05
15.0	6.00	1.05
16.0	6.00	1.05
17.0	6.01	1.04
18.0	6.03	1.03
19.0	6.03	1.03
20.0	6.01	1.04
21.0	6.00	1.04
22.0	5.98	1.03
23.0	5.97	1.04
24.0	5.95	1.04
25.0	5.94	1.04
26.0	5.94	1.04
27.0	5.97	1.05
28.0	6.00	1.05
29.0	5.99	1.05
30.0	5.98	1.05
31.0	5.98	1.05
32.0	6.00	1.05
33.0	5.98	1.06
34.0	5.97	1.07
35.0	5.96	1.07
36.0	5.97	1.07
37.0	5.83	1.07
38.0	5.78	1.08
39.0	5.75	1.09
40.0	5.75	1.10
41.0	5.68	1.10
42.0	5.68	1.11
43.0	5.67	1.11
43.5	5.68	1.12