

*Typical Performance Data***NOTE: Use PDF Bookmarks to view DATA at required conditions****Definitions:**

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 108.42mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.44	24.16	12.65	11.75	1.24	0.72	39.39	19.88	5.94
20.0	17.74	23.83	14.82	16.54	1.22	0.74	40.65	19.08	4.04
30.0	17.78	23.84	15.06	18.87	1.23	0.75	40.91	19.18	3.24
40.0	17.80	23.80	15.57	20.07	1.23	0.75	40.98	19.33	3.16
50.0	17.91	23.69	15.35	21.73	1.21	0.74	40.05	19.41	2.99
60.0	17.80	23.81	16.03	20.82	1.23	0.75	40.06	19.32	2.86
80.0	17.79	23.79	15.64	21.16	1.23	0.75	40.69	19.37	3.09
90.0	17.78	23.78	15.59	21.14	1.23	0.75	39.98	19.41	2.89
100.0	17.78	23.80	15.59	21.06	1.23	0.76	40.90	19.44	2.82
150.0	17.74	23.82	15.75	19.99	1.23	0.75	40.18	19.54	2.82
200.0	17.73	23.85	15.44	19.56	1.24	0.76	40.35	19.58	2.78
250.0	17.69	23.87	15.09	19.49	1.24	0.76	40.37	19.78	2.89
300.0	17.64	23.92	15.12	19.13	1.25	0.77	39.64	19.71	2.95
350.0	17.59	23.94	15.36	17.99	1.25	0.76	39.60	20.02	2.99
400.0	17.53	24.00	15.17	16.96	1.26	0.76	39.37	20.17	3.15
500.0	17.38	24.12	14.10	15.56	1.27	0.77	38.80	20.02	2.89
600.0	17.26	24.21	14.48	14.94	1.29	0.77	38.44	19.52	2.86
700.0	17.16	24.27	15.28	16.13	1.32	0.79	37.85	19.22	2.95
800.0	17.08	24.33	17.70	15.51	1.34	0.78	37.50	19.67	3.29
900.0	17.04	24.34	18.21	14.64	1.33	0.78	37.82	20.03	3.12
1000.0	16.99	24.37	20.94	14.91	1.35	0.78	37.29	20.29	3.03
1100.0	16.89	24.43	29.74	16.57	1.37	0.80	37.56	20.52	3.08
1200.0	16.76	24.56	30.81	14.88	1.39	0.81	36.62	19.98	3.17
1300.0	16.57	24.75	21.13	13.54	1.39	0.82	36.07	19.63	3.26
1400.0	16.37	24.93	21.59	13.06	1.43	0.83	35.86	19.64	3.46
1500.0	16.16	25.14	19.61	13.63	1.49	0.86	36.06	19.72	3.42
1600.0	15.95	25.38	18.24	12.19	1.51	0.86	35.96	19.11	3.33
1700.0	15.75	25.60	16.34	11.05	1.52	0.87	35.47	18.83	3.48
1800.0	15.62	25.75	18.08	10.89	1.58	0.85	35.39	18.86	3.61
1900.0	15.53	25.91	18.50	12.98	1.67	0.89	35.55	19.66	4.08
2000.0	15.37	26.11	13.36	15.87	1.72	0.95	35.60	20.63	3.76

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 4.75V, Id = 97.49mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.41	24.14	12.76	11.71	1.24	0.72	40.31	19.65	5.78
20.0	17.70	23.85	14.76	16.47	1.23	0.74	39.11	18.87	3.94
30.0	17.73	23.81	15.04	18.71	1.23	0.75	39.36	18.99	3.10
40.0	17.75	23.78	15.11	19.86	1.23	0.75	39.81	19.12	3.09
50.0	17.88	23.65	16.84	21.45	1.21	0.74	40.30	19.19	2.91
60.0	17.75	23.76	15.93	20.54	1.23	0.75	41.15	19.12	2.79
80.0	17.75	23.77	15.55	20.84	1.23	0.75	40.12	19.19	3.01
90.0	17.74	23.77	15.51	20.84	1.23	0.75	40.35	19.23	2.80
100.0	17.74	23.77	15.52	20.77	1.23	0.76	40.22	19.26	2.73
150.0	17.70	23.80	15.53	19.75	1.24	0.76	40.19	19.34	2.75
200.0	17.69	23.83	15.28	19.32	1.24	0.76	39.90	19.39	2.75
250.0	17.65	23.86	15.02	19.25	1.24	0.76	39.84	19.57	2.85
300.0	17.59	23.88	15.06	18.90	1.25	0.76	39.61	19.50	2.92
350.0	17.55	23.91	15.22	17.80	1.25	0.76	39.52	19.79	2.91
400.0	17.48	23.97	15.04	16.79	1.26	0.76	39.12	19.94	3.07
500.0	17.34	24.08	13.97	15.40	1.27	0.77	38.93	19.80	2.82
600.0	17.22	24.18	14.37	14.80	1.29	0.77	38.03	19.30	2.80
700.0	17.11	24.25	15.16	15.97	1.32	0.79	38.05	19.06	2.91
800.0	17.03	24.31	17.61	15.37	1.34	0.78	37.78	19.48	3.40
900.0	17.00	24.30	18.07	14.48	1.33	0.78	37.99	19.82	3.09
1000.0	16.95	24.33	20.58	14.75	1.35	0.78	37.22	20.04	3.01
1100.0	16.86	24.39	29.44	16.39	1.37	0.80	37.31	20.28	3.03
1200.0	16.72	24.51	31.72	14.75	1.38	0.80	36.71	19.79	3.10
1300.0	16.53	24.70	21.26	13.40	1.39	0.82	36.44	19.40	3.20
1400.0	16.33	24.88	21.70	12.93	1.43	0.83	36.18	19.34	3.39
1500.0	16.13	25.09	19.71	13.48	1.48	0.85	36.38	19.41	3.38
1600.0	15.91	25.32	18.34	12.07	1.50	0.86	36.44	18.78	3.28
1700.0	15.72	25.55	16.48	10.94	1.51	0.86	36.17	18.52	3.44
1800.0	15.59	25.71	18.23	10.79	1.58	0.85	36.14	18.57	3.53
1900.0	15.50	25.84	18.73	12.87	1.66	0.88	36.08	19.38	4.01
2000.0	15.34	26.06	13.42	15.63	1.71	0.95	35.80	20.36	3.74

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 119.54mA @ Temperature = +25°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.51	24.04	14.13	11.75	1.23	0.70	39.60	20.08	6.06
20.0	17.78	23.88	15.00	16.62	1.23	0.74	38.59	19.17	4.15
30.0	17.81	23.83	15.18	19.00	1.23	0.75	39.43	19.26	3.28
40.0	17.83	23.82	15.48	20.23	1.23	0.75	39.35	19.43	3.25
50.0	17.96	23.80	17.02	21.96	1.22	0.74	38.81	19.55	3.06
60.0	17.83	23.76	15.89	20.97	1.22	0.75	39.88	19.41	2.96
80.0	17.82	23.80	15.79	21.33	1.23	0.75	38.75	19.46	3.18
90.0	17.81	23.80	15.75	21.33	1.23	0.75	38.41	19.50	2.94
100.0	17.81	23.81	15.76	21.25	1.23	0.75	39.21	19.52	2.85
150.0	17.77	23.87	15.94	20.21	1.24	0.75	38.57	19.62	2.84
200.0	17.76	23.87	15.53	19.73	1.24	0.76	38.43	19.69	2.86
250.0	17.72	23.89	15.20	19.67	1.24	0.76	37.94	19.87	2.96
300.0	17.67	23.91	15.25	19.30	1.24	0.76	38.64	19.81	3.00
350.0	17.62	23.96	15.41	18.14	1.25	0.76	38.63	20.13	3.04
400.0	17.56	24.02	15.31	17.10	1.26	0.76	38.44	20.29	3.17
500.0	17.41	24.13	14.18	15.67	1.27	0.77	38.32	20.14	2.92
600.0	17.30	24.23	14.55	15.06	1.29	0.77	37.23	19.62	2.89
700.0	17.19	24.29	15.40	16.27	1.32	0.79	36.77	19.27	2.98
800.0	17.11	24.33	17.83	15.66	1.33	0.78	36.69	19.74	3.38
900.0	17.07	24.37	18.35	14.76	1.33	0.78	37.05	20.14	3.15
1000.0	17.03	24.39	20.84	15.06	1.35	0.78	36.83	20.44	3.09
1100.0	16.93	24.46	30.30	16.79	1.37	0.80	36.95	20.65	3.15
1200.0	16.79	24.59	30.57	15.09	1.39	0.81	35.91	20.04	3.16
1300.0	16.60	24.78	20.98	13.70	1.40	0.83	35.41	19.74	3.33
1400.0	16.41	24.97	21.43	13.22	1.44	0.83	35.20	19.80	3.49
1500.0	16.20	25.18	19.45	13.80	1.49	0.86	35.39	19.90	3.46
1600.0	15.99	25.42	18.18	12.36	1.51	0.86	35.23	19.36	3.39
1700.0	15.80	25.64	16.27	11.18	1.52	0.87	34.81	19.09	3.53
1800.0	15.66	25.81	17.99	11.00	1.59	0.85	34.66	19.09	3.64
1900.0	15.57	25.97	18.36	13.10	1.68	0.89	34.79	19.86	4.11
2000.0	15.41	26.17	13.34	16.14	1.72	0.95	34.97	20.83	3.78

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 95.93mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.29	24.01	12.03	10.76	1.23	0.70	39.32	20.28	7.26
20.0	17.62	23.69	13.91	15.33	1.22	0.73	46.84	19.40	4.07
30.0	17.66	23.67	14.28	17.33	1.22	0.74	43.88	19.46	2.66
40.0	17.67	23.65	14.26	18.14	1.22	0.75	42.35	19.63	2.30
50.0	17.79	23.50	15.32	19.14	1.20	0.73	45.45	19.76	2.04
60.0	17.66	23.66	14.84	18.19	1.22	0.74	43.58	19.65	1.87
80.0	17.66	23.65	14.18	18.03	1.22	0.75	47.47	19.74	2.10
90.0	17.65	23.63	14.26	17.96	1.22	0.74	45.56	19.78	1.86
100.0	17.65	23.64	14.23	17.93	1.22	0.74	45.30	19.81	1.75
150.0	17.63	23.69	14.89	18.30	1.23	0.75	46.42	19.88	1.82
200.0	17.63	23.65	15.31	19.04	1.23	0.75	43.28	19.93	1.89
250.0	17.61	23.66	14.92	18.25	1.23	0.75	42.18	20.13	1.96
300.0	17.53	23.73	14.78	17.26	1.24	0.75	42.18	20.06	2.04
350.0	17.52	23.72	14.69	16.31	1.23	0.75	41.76	20.35	2.04
400.0	17.46	23.79	14.32	15.45	1.24	0.75	41.49	20.51	2.17
500.0	17.34	23.86	12.69	13.72	1.24	0.75	40.77	20.37	1.90
600.0	17.25	23.93	13.53	14.11	1.26	0.75	39.48	19.90	1.88
700.0	17.17	23.97	14.91	15.44	1.29	0.77	38.47	19.66	1.96
800.0	17.12	23.98	18.04	15.21	1.30	0.76	37.98	20.09	2.47
900.0	17.13	23.97	17.22	13.08	1.27	0.75	38.30	20.47	2.11
1000.0	17.08	23.99	18.60	13.40	1.29	0.75	37.69	20.63	1.97
1100.0	16.97	24.05	24.64	15.67	1.32	0.77	38.02	20.86	2.04
1200.0	16.85	24.18	33.42	14.95	1.34	0.78	36.74	20.45	2.11
1300.0	16.66	24.35	19.76	12.36	1.31	0.80	35.71	20.07	2.18
1400.0	16.47	24.53	19.79	11.53	1.34	0.80	35.39	19.97	2.35
1500.0	16.30	24.70	21.39	12.01	1.40	0.81	35.67	20.19	2.30
1600.0	16.13	24.90	21.09	12.57	1.45	0.83	35.47	19.56	2.17
1700.0	15.99	25.06	17.45	11.91	1.45	0.85	35.00	19.18	2.36
1800.0	15.91	25.17	17.18	10.92	1.45	0.84	34.92	19.17	2.41
1900.0	15.82	25.30	16.53	11.11	1.47	0.86	35.16	20.00	3.00
2000.0	15.65	25.54	14.49	13.05	1.55	0.91	35.13	21.03	2.58

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 4.75V, Id = 84.64mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.21	24.04	11.89	10.74	1.23	0.71	39.08	19.81	6.75
20.0	17.52	23.62	13.77	15.09	1.22	0.73	43.28	19.04	3.74
30.0	17.56	23.61	13.83	16.94	1.22	0.74	44.55	19.10	2.44
40.0	17.58	23.59	14.10	17.66	1.22	0.75	43.56	19.25	2.18
50.0	17.70	23.57	14.86	18.62	1.21	0.74	45.08	19.38	1.96
60.0	17.57	23.62	14.48	17.67	1.22	0.75	46.74	19.30	1.77
80.0	17.56	23.58	14.04	17.53	1.22	0.74	43.65	19.38	2.04
90.0	17.56	23.57	14.05	17.46	1.22	0.74	43.29	19.43	1.83
100.0	17.56	23.58	13.97	17.44	1.22	0.74	44.61	19.46	1.77
150.0	17.54	23.60	14.70	17.82	1.23	0.75	43.81	19.53	1.81
200.0	17.54	23.60	15.10	18.50	1.23	0.75	42.55	19.56	1.81
250.0	17.51	23.62	14.58	17.76	1.23	0.75	41.09	19.73	1.96
300.0	17.44	23.68	14.56	16.87	1.24	0.75	41.48	19.68	2.02
350.0	17.43	23.67	14.44	15.93	1.23	0.75	40.72	19.95	1.99
400.0	17.37	23.73	14.07	15.08	1.24	0.75	40.97	20.08	2.16
500.0	17.25	23.81	12.57	13.44	1.24	0.75	39.80	19.95	1.86
600.0	17.16	23.87	13.30	13.81	1.26	0.75	38.98	19.52	1.84
700.0	17.08	23.92	14.66	15.12	1.29	0.77	38.05	19.34	1.86
800.0	17.03	23.93	17.59	14.91	1.30	0.76	37.68	19.74	2.44
900.0	17.04	23.90	16.96	12.83	1.27	0.75	38.22	20.09	2.07
1000.0	16.99	23.92	18.19	13.14	1.29	0.74	37.20	20.19	1.98
1100.0	16.89	24.00	23.95	15.36	1.32	0.77	37.29	20.42	2.05
1200.0	16.77	24.11	35.91	14.78	1.34	0.78	36.32	20.06	2.09
1300.0	16.58	24.28	19.86	12.20	1.31	0.80	35.55	19.64	2.15
1400.0	16.39	24.47	19.77	11.37	1.33	0.80	35.21	19.47	2.33
1500.0	16.22	24.63	21.41	11.82	1.39	0.81	35.49	19.68	2.27
1600.0	16.05	24.82	21.40	12.40	1.45	0.83	35.36	19.11	2.14
1700.0	15.92	24.98	17.63	11.75	1.44	0.85	34.85	18.77	2.29
1800.0	15.83	25.09	17.29	10.76	1.44	0.84	34.65	18.78	2.38
1900.0	15.75	25.22	16.59	10.93	1.46	0.85	34.89	19.62	2.97
2000.0	15.58	25.43	14.60	12.84	1.54	0.90	34.84	20.57	2.56

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 106.97mA @ Temperature = -45°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.38	23.92	12.48	10.86	1.21	0.69	42.05	20.61	7.71
20.0	17.69	23.73	14.00	15.55	1.21	0.73	49.08	19.68	4.43
30.0	17.72	23.70	14.34	17.61	1.22	0.74	45.60	19.73	2.83
40.0	17.74	23.70	14.51	18.46	1.22	0.74	43.30	19.89	2.48
50.0	17.86	23.74	14.56	19.60	1.21	0.75	44.06	19.99	2.12
60.0	17.73	23.71	14.41	18.54	1.22	0.75	45.92	19.90	1.94
80.0	17.73	23.68	14.37	18.39	1.22	0.74	44.69	19.97	2.13
90.0	17.72	23.68	14.44	18.32	1.22	0.74	44.89	20.01	1.88
100.0	17.72	23.68	14.44	18.31	1.22	0.74	44.45	20.05	1.77
150.0	17.70	23.71	15.01	18.73	1.23	0.75	46.43	20.13	1.80
200.0	17.70	23.70	15.44	19.46	1.23	0.75	42.70	20.18	1.83
250.0	17.68	23.71	15.17	18.63	1.23	0.75	42.62	20.39	1.92
300.0	17.60	23.77	15.00	17.65	1.23	0.75	42.07	20.32	2.02
350.0	17.59	23.76	14.95	16.60	1.23	0.75	41.39	20.63	2.03
400.0	17.53	23.82	14.45	15.65	1.23	0.75	41.24	20.79	2.14
500.0	17.41	23.91	12.80	13.95	1.24	0.75	40.79	20.66	1.89
600.0	17.32	23.97	13.59	14.32	1.26	0.75	39.44	20.16	1.83
700.0	17.24	24.01	15.15	15.72	1.28	0.77	38.31	19.89	1.92
800.0	17.19	24.03	18.23	15.45	1.29	0.76	38.05	20.33	2.45
900.0	17.20	24.01	17.44	13.25	1.27	0.75	38.32	20.75	2.09
1000.0	17.15	24.03	18.87	13.61	1.29	0.75	38.07	20.95	2.03
1100.0	17.04	24.10	25.38	15.91	1.32	0.78	37.66	21.19	2.03
1200.0	16.92	24.22	32.18	15.18	1.34	0.79	36.68	20.72	2.09
1300.0	16.72	24.39	19.46	12.44	1.31	0.80	35.96	20.36	2.16
1400.0	16.53	24.59	19.69	11.69	1.34	0.81	35.53	20.33	2.36
1500.0	16.36	24.75	21.22	12.14	1.39	0.82	35.87	20.57	2.36
1600.0	16.20	24.94	21.13	12.79	1.45	0.84	35.60	19.90	2.20
1700.0	16.06	25.11	17.50	12.09	1.45	0.85	35.18	19.52	2.35
1800.0	15.98	25.22	17.12	11.07	1.45	0.85	34.84	19.49	2.44
1900.0	15.89	25.35	16.31	11.23	1.47	0.86	35.06	20.32	2.99
2000.0	15.71	25.59	14.33	13.21	1.55	0.91	35.25	21.37	2.61

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.00V, Id = 114.60mA @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.33	23.94	13.12	12.08	1.24	0.72	35.46	19.42	6.49
20.0	17.59	23.80	14.80	16.54	1.23	0.75	33.61	18.53	4.60
30.0	17.63	23.77	15.28	18.59	1.23	0.75	33.82	18.59	3.85
40.0	17.65	23.76	15.50	19.72	1.23	0.76	34.34	18.78	3.78
50.0	17.77	23.62	16.27	21.46	1.22	0.74	34.34	18.89	3.68
60.0	17.65	23.74	16.53	20.79	1.24	0.75	34.01	18.73	3.55
80.0	17.64	23.73	16.07	21.59	1.24	0.76	33.77	18.80	3.79
90.0	17.63	23.73	16.03	21.68	1.24	0.76	33.62	18.83	3.59
100.0	17.63	23.76	15.95	21.60	1.24	0.76	33.81	18.86	3.54
150.0	17.58	23.82	15.67	19.58	1.25	0.76	34.07	18.98	3.62
200.0	17.55	23.82	14.85	18.57	1.25	0.76	34.01	19.04	3.64
250.0	17.51	23.85	14.70	19.18	1.25	0.77	34.02	19.21	3.76
300.0	17.46	23.88	15.00	19.65	1.26	0.78	34.12	19.16	3.81
350.0	17.39	23.95	15.42	18.38	1.27	0.78	34.43	19.46	3.85
400.0	17.31	24.02	15.38	17.13	1.28	0.78	34.49	19.61	3.97
500.0	17.16	24.14	14.66	16.19	1.30	0.79	34.41	19.42	3.73
600.0	17.01	24.27	14.54	14.51	1.32	0.78	33.56	18.88	3.70
700.0	16.88	24.36	14.84	15.64	1.35	0.80	32.94	18.54	3.84
800.0	16.79	24.43	17.42	15.55	1.38	0.80	33.20	19.01	4.34
900.0	16.73	24.47	18.72	16.50	1.39	0.81	33.70	19.39	4.01
1000.0	16.70	24.50	22.08	14.93	1.39	0.80	34.16	19.69	3.95
1100.0	16.63	24.55	26.88	15.34	1.41	0.81	34.64	19.91	3.96
1200.0	16.48	24.69	30.11	14.48	1.43	0.82	33.93	19.30	4.09
1300.0	16.27	24.91	22.18	15.42	1.48	0.85	33.57	19.00	4.17
1400.0	16.06	25.13	22.46	14.29	1.52	0.85	33.37	19.02	4.39
1500.0	15.83	25.37	18.80	13.62	1.56	0.87	33.65	19.07	4.37
1600.0	15.58	25.66	16.25	11.05	1.55	0.87	33.64	18.63	4.29
1700.0	15.34	25.92	14.96	10.60	1.60	0.88	33.14	18.38	4.48
1800.0	15.18	26.15	17.82	10.95	1.73	0.86	32.95	18.41	4.61
1900.0	15.08	26.31	20.13	13.98	1.85	0.90	33.21	19.17	5.01
2000.0	14.94	26.50	12.40	16.64	1.85	0.98	33.76	20.10	4.76

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 4.75V, Id = 103.87mA @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.28	23.99	13.26	12.07	1.24	0.73	35.96	19.30	6.34
20.0	17.56	23.80	14.89	16.47	1.24	0.75	35.26	18.42	4.48
30.0	17.60	23.77	15.08	18.47	1.24	0.76	35.84	18.49	3.67
40.0	17.62	23.72	15.41	19.58	1.23	0.76	36.40	18.67	3.69
50.0	17.74	23.74	15.95	21.33	1.23	0.75	36.11	18.77	3.53
60.0	17.62	23.66	16.37	20.62	1.23	0.75	35.59	18.65	3.45
80.0	17.61	23.72	15.87	21.39	1.24	0.76	35.89	18.72	3.68
90.0	17.61	23.72	15.93	21.49	1.24	0.76	35.63	18.75	3.52
100.0	17.60	23.72	15.85	21.40	1.24	0.76	35.61	18.78	3.46
150.0	17.55	23.77	15.52	19.39	1.24	0.76	35.89	18.88	3.54
200.0	17.53	23.81	14.76	18.44	1.25	0.76	35.89	18.93	3.55
250.0	17.48	23.84	14.57	19.03	1.25	0.77	35.67	19.10	3.69
300.0	17.43	23.87	14.96	19.49	1.26	0.78	35.95	19.06	3.72
350.0	17.36	23.93	15.40	18.27	1.27	0.78	36.01	19.34	3.77
400.0	17.29	23.99	15.22	17.06	1.28	0.78	36.17	19.48	3.91
500.0	17.13	24.12	14.51	16.08	1.30	0.79	35.84	19.30	3.67
600.0	16.98	24.26	14.45	14.39	1.32	0.78	35.45	18.78	3.66
700.0	16.85	24.34	14.69	15.52	1.35	0.80	34.75	18.49	3.76
800.0	16.76	24.41	17.19	15.48	1.38	0.80	34.89	18.95	4.04
900.0	16.71	24.45	18.65	16.42	1.39	0.81	35.10	19.30	3.94
1000.0	16.67	24.47	22.02	14.76	1.39	0.80	35.28	19.55	3.88
1100.0	16.60	24.52	26.65	15.16	1.40	0.81	35.66	19.78	3.93
1200.0	16.45	24.67	30.23	14.35	1.43	0.82	35.17	19.21	3.99
1300.0	16.25	24.88	22.39	15.32	1.48	0.85	34.75	18.86	4.10
1400.0	16.03	25.09	22.59	14.15	1.52	0.85	34.57	18.83	4.35
1500.0	15.80	25.33	18.90	13.47	1.56	0.87	34.70	18.85	4.32
1600.0	15.55	25.63	16.37	10.93	1.55	0.87	34.66	18.37	4.24
1700.0	15.31	25.89	15.03	10.55	1.60	0.88	34.36	18.13	4.43
1800.0	15.15	26.10	17.88	10.92	1.72	0.86	34.19	18.17	4.53
1900.0	15.05	26.27	20.36	13.93	1.85	0.90	34.22	18.95	4.98
2000.0	14.91	26.43	12.51	16.37	1.84	0.98	34.60	19.90	4.72

Typical Performance Data

Definitions:

Input Return Loss = -S11 (dB)

Gain(Power Gain) = S21 (dB)

Reverse Isolation = -S12 (dB)

Output Return Loss = -S22 (dB)

TEST CONDITIONS: Vd = 5.25V, Id = 125.28mA @ Temperature = +85°C

FREQ	Gain	Isolation	Input Return Loss	Output Return Loss	Stability		IP-3 Output	1dB Comp. Output	Noise Figure
					K	Measure			
(MHz)	(dB)	(dB)	(dB)	(dB)	K	Measure	(dBm)	(dBm)	(dB)
10.0	17.34	24.02	14.13	12.14	1.25	0.72	31.93	19.37	6.59
20.0	17.57	23.80	14.92	16.59	1.24	0.75	31.24	18.47	4.64
30.0	17.61	23.78	15.32	18.64	1.24	0.76	31.61	18.54	3.85
40.0	17.63	23.77	15.57	19.81	1.24	0.76	31.84	18.74	3.82
50.0	17.76	23.61	17.24	21.53	1.22	0.74	31.67	18.85	3.66
60.0	17.63	23.76	15.88	20.92	1.24	0.76	31.46	18.69	3.55
80.0	17.62	23.75	16.14	21.73	1.24	0.76	31.18	18.69	3.56
90.0	17.61	23.74	16.11	21.82	1.24	0.76	31.06	18.71	3.47
100.0	17.61	23.76	16.09	21.73	1.24	0.76	31.21	18.74	3.47
150.0	17.56	23.80	15.61	19.64	1.25	0.76	31.38	18.92	3.57
200.0	17.53	23.85	14.91	18.69	1.25	0.77	31.52	18.95	3.59
250.0	17.49	23.87	14.75	19.30	1.25	0.77	31.55	19.15	3.67
300.0	17.44	23.90	15.17	19.77	1.26	0.78	31.73	19.08	3.73
350.0	17.37	23.96	15.46	18.56	1.28	0.78	32.07	19.41	3.76
400.0	17.29	24.02	15.40	17.33	1.28	0.78	32.18	19.54	3.98
500.0	17.14	24.16	14.60	16.30	1.30	0.79	31.93	19.32	3.80
600.0	16.99	24.30	14.58	14.56	1.33	0.79	31.11	18.70	3.71
700.0	16.86	24.38	14.83	15.73	1.36	0.80	30.56	18.36	3.83
800.0	16.77	24.45	17.30	15.73	1.38	0.80	30.76	18.81	4.11
900.0	16.72	24.51	18.68	16.74	1.40	0.82	31.37	19.28	4.01
1000.0	16.69	24.53	22.07	15.01	1.40	0.80	32.17	19.66	3.92
1100.0	16.61	24.57	26.31	15.48	1.41	0.81	32.59	19.89	3.99
1200.0	16.46	24.74	29.85	14.66	1.44	0.82	31.89	19.27	4.09
1300.0	16.26	24.94	21.88	15.74	1.49	0.85	31.48	19.00	4.19
1400.0	16.04	25.17	22.16	14.48	1.53	0.86	31.31	19.04	4.36
1500.0	15.81	25.42	18.69	13.79	1.57	0.88	31.59	19.17	4.40
1600.0	15.56	25.72	16.17	11.15	1.56	0.88	31.63	18.80	4.36
1700.0	15.33	25.98	14.75	10.75	1.62	0.88	31.18	18.53	4.52
1800.0	15.16	26.21	17.55	11.07	1.74	0.87	30.97	18.52	4.63
1900.0	15.06	26.38	19.85	14.12	1.87	0.91	31.27	19.27	5.11
2000.0	14.92	26.58	12.32	16.89	1.87	0.98	32.17	20.18	4.86