

PRODUCT CHANGE NOTICE

PCN Form (D4-E000-73)

PCN#25-040**NOTIFICATION DATE: June 19, 2025****MODEL(S) AFFECTED:****RCDAT-4000-120****RUDAT-4000-120****EXTENT OF CHANGE:**

Replacement of supplied attenuator chip, based on discontinuation of supply, with alternate qualified chip from same supplier.

EFFECT OF CHANGE:

- No change in FIT.
- Change in Function – performance and specifications vary from original performance as follows:

Parameters	Conditions (MHz)	Old design	New design
Return Loss In @ 0 - 20 dB	1 - 500	17.7 dB Typ	15 dB Typ
	500 - 4000	26.4 dB Typ	23 dB Typ
Return Loss In @ 20.25 - 40 dB	1 - 500	17.7 dB Typ	23 dB Typ
	500 - 4000	32.2 dB Typ	
Return Loss In @ 40.25 - 120 dB	1 - 4000	32.2 dB Typ	
Return Loss Out @ 0 - 10 dB	1 - 500	17.7 dB Typ	15 dB Typ
	500 - 3500	26.4 dB Typ	23 dB Typ
	3500 - 4000	26.4 dB Typ	15 dB Typ
Return Loss Out @ 10.25 - 20 dB	1 - 500	17.7 dB Typ	17 dB Typ
	500 - 4000	26.4 dB Typ	
Return Loss Out @ 20.25 - 40 dB	1 - 500	17.7 dB Typ	
	500 - 4000	32.2 dB Typ	
Return Loss Out @ 40.25 - 120 dB	1 - 4000	32.2 dB Typ	
Input operating power	1 - 10	+10 dBm Max	Derates linearly from +23 dBm at 50 MHz to +9 dBm at 1 MHz.
	10 - 50	+20 dBm Max	
	50 - 4000	+20 dBm Max	+23 dBm Max
Max RF Power @ Abs. Max Ratings	1 - 10	+13 dBm Max	Derates linearly from +26 dBm at 50 MHz to +12 dBm at 1 MHz.
	10 - 50	+23 dBm Max	
	50 - 4000	+23 dBm Max	+26 dBm Max

PRODUCT CHANGE NOTICE

PCN Form (D4-E000-73)

- Change in Form – (Cosmetic change only) Changed power warning on label:



REASON FOR CHANGE:

Obsolescence of supplied components.

EFFECTIVE DATE OF CHANGE:

On exhaustion of existing stock. First date code after change is 2524.

QUESTIONS?

[PLEASE CONTACT US.](#)