



STRIPLINE SURFACE MOUNT

Power Splitter/Combiner

QCH-43+

Mini-Circuits

50Ω 2000 to 4000 MHz 2-Way 90° 200W

KEY FEATURES

- High power handling, up to 200W
- Over octave bandwidth, 2000 to 4000 MHz
- Low insertion loss, 0.15 dB typ

APPLICATIONS

- Balanced amplifiers
- I&Q modulators
- Defense and military


PRODUCT OVERVIEW

Mini-Circuits' QCH-43+ is a 2-way 90° power splitter, capable of handling up to 200W with amplitude unbalance of ± 0.35 dB typ and phase unbalance of ± 1.0 deg. typ. Operating over a frequency range of 2000 to 4000 MHz, the outstanding phase and amplitude unbalance make this component a versatile building block for use in a variety of systems and sub-system designs from balanced amplifiers and antenna feeds to military applications and more. The splitter is fabricated using laminated PCB process (0.56 x 0.35 x 0.09") and includes wrap-around terminations for good solderability and easy visual inspection.



Generic photo used for illustration purposes only

FUNCTIONAL DIAGRAM



ELECTRICAL SPECIFICATIONS AT +25°C^{1,2}

Parameter	Conditions (MHz)	Min.	Typ.	Max.	Unit
Frequency Range	-	2000	-	4000	MHz
Insertion Loss ³	2000 - 4000	-	0.15	0.35	dB
Isolation	2000 - 4000	18	27	-	dB
Phase Unbalance	2000 - 4000	-	± 1.00	± 5.00	deg
Amplitude Unbalance	2000 - 4000	-	± 0.35	± 0.50	dB
Return Loss	2000 - 4000	17.5	25.0	-	dB
Thermal Resistance ⁴	2000 - 4000	-	0.35	-	°C/W

1. Tested in Evaluation Board TB-1077+. De-embedded to the device reference plane.

2. Model is symmetrical and all ports are interchangeable, see Port Function Description/Configuration table for details and S-Parameters for actual performance.

3. Does not include theoretical loss due to coupling. Nominal theoretical loss is 3 dB.

4. Thermal Resistance is defined as $\theta_{jc} = (\text{Hot Spot Temperature on DUT} - \text{Base Plate Temperature}) / \text{Input Power}$.

ABSOLUTE MAXIMUM RATINGS⁵

Operating Case Temperature ⁶	-55°C to +105°C	
Storage Temperature	-55°C to +105°C	
Power Input	+85°C case	200 W
	+95°C case	150 W
	+105°C case	120 W

5. Permanent damage may occur if any of these limits are exceeded.

6. Case temperature is defined as temperature on base plate.





STRIPLINE SURFACE MOUNT







Power Splitter/Combiner

QCH-43+

Mini-Circuits

50Ω 2000 to 4000 MHz 2-Way 90° 200W

TYPICAL PERFORMANCE GRAPHS*



* Data corresponds to Configuration A at +25°C unless otherwise specified.





STRIPLINE SURFACE MOUNT


Power Splitter/Combiner

QCH-43+

Mini-Circuits

50Ω 2000 to 4000 MHz 2-Way 90° 200W

FUNCTIONAL DIAGRAM




PAD DESCRIPTION/CONFIGURATION 7

Function	Pad	Description
Sum	1	Sum port
Isolation	2	Isolation port
Port 1 (0°)	3	0° port
Port 2 (90°)	4	90° port
Ground	5	Ground

Configuration	Sum	Isolation	Port 1 (0°)	Port 2 (90°)
A	1	2	3	4
B	2	1	4	3
C	3	4	1	2
D	4	3	2	1

7. Model is symmetrical and all ports are interchangeable, see Port Function Configurations table and s-parameters for actual performance.

SUGGESTED PCB LAYOUT (PL-605)





NOTES:


1. TRACE WIDTH IS SHOWN FOR ROGERS RO4003C WITH DIELECTRIC THICKNESS 0.032"±.0015". COPPER: 1 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDERMASK

CASE STYLE DRAWING (PQ2186-9)



PCB Land Pattern



- METALIZATION
- SOLDER RESIST

NOTES:

1. Base material: Printed wiring laminate.
2. Termination finish: 2-5 μinch (.05-.13 microns) Immersion Gold.
3. Dimensions: Inches [mm]. Tolerances 2 Pl. ±.03 inch; 3 Pl. ±.010 inch.
4. Weight: 1.4 grams
5. Marking may contain other features or characters for internal lot control.

PRODUCT MARKING*: QCH-43+

* Marking may contain other features or characters for internal lot control.

Mini-Circuits



STRIPLINE SURFACE MOUNT

Power Splitter/Combiner

QCH-43+



50Ω 2000 to 4000 MHz 2-Way 90° 200W

ADDITIONAL DETAILED INFORMATION IS AVAILABLE ON OUR DASH BOARD

[CLICK HERE](#)

Performance Data & Graphs	Data Graphs S-Parameter (S4P files) data set (.zip file) de-embedded to device pads
Case Style	PQ2186-9 Lead finish: 2-5 μ inch (0.05-0.13 microns) immersion gold
RoHS Status	Compliant
Tape and Reel	F29
Suggested Layout for PCB Design	PL-605
Evaluation Board	TB-QCH-43+ Gerber file
Environmental Rating	ENV02T8

NOTES:

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at <https://www.minicircuits.com/terms/viewterm.html>

